

Roof-Fast™



SELF-ADHERING MEMBRANES (SAM) RESIDENTIAL LOW SLOPE ROOF SYSTEM

Description/Uses

Roof-Fast is a low slope roofing material that combines the polymer chemistry of commercial-grade modified bitumen membranes with the self-adhesive characteristics of an ice and water shield and the beauty of a granule surface.

This self-adhering membrane (SAM) system is comprised of two elements:

Roof-Fast Cap

A fiberglass reinforced self-adhesive cap sheet coated with a granule surface and a release film on the backside. It's available in several popular colors and comes in a one square roll which may be used alone or in combination with Roof-Fast Base.

- Roll dimensions: 39.375 inches x 32.92 feet (1000 millimeters x 10.03 meters)
- Area: 100 square feet (9.29 square meters)

Roof-Fast Base

A fiberglass reinforced self-adhesive base sheet with a special film surface designed for use with Roof-Fast Cap self-adhering cap sheet.

- Roll dimensions: 39.375 inches x 65.92 feet (1000 millimeters x 20.09 meters)
- Area: 200 square feet (18.58 square meters)

The Roof-Fast system is designed for use on new or existing low-slope roofs and is suitable for most low-slope applications where the use of adhesives, propane torches, or hot asphalt is impractical, undesirable, or unsafe.

Tools and Accessories for Installation

Roofers' cutting tool · T-Square · Chalk line · 60 – 100 pounds (27-45 kilograms) Steel roller · IKO S.A.M. Adhesive primer or IKO S.A.M. Adhesive LVC primer · Roofing Trowel · IKO AquaBarrier Mastic · IKO EdgeSeal · High-Grade Exterior Caulk



Working on a sloped roof can be dangerous; avoid slip and fall hazards by taking proper precautions. Use appropriate safety measures, such as safety harnesses, when applying the product. **IMPORTANT:** Use and application of this product must be in accordance with all local building code requirements.

Features & Benefits

- Easy, self-adhering peel and stick application.
- One-ply, two-ply self adhered or two-ply mechanically adhered application.
- No hot asphalt, torch or odor.
- Attractive, durable ceramic granule finish.
- Uses polymer-modified asphalt instead of traditional oxidized asphalt.
- Appropriate for most low-slope roofs (see installation instructions for specific system minimum slope limitations). For slopes over 4:12, please contact IKO.
- Available with an 8-year (single-ply), 12-year (two-ply Mechanically Attached), or 15-year (two-ply Self Adhered) Limited Material Warranty.

Note: While the digital color swatches aim for accuracy, they don't capture the entire Roof-Fast Cap color range. For best results, choose your color from a full-size roll and view a sample on a home for complete satisfaction.



Application Instructions



Warranty



Black



Slate Grey



White



Driftwood



Dual Brown

Note: While the digital color swatches aim for total accuracy, they don't capture the entire Roof-Fast Cap color range. For best results, choose your color from a full-size roll and view a sample on a home for complete satisfaction.